

## Zaptivna pletenica tip 2026

### Sastav materijala:

Zaptivna pletenica dijagonalnog pletenja, proizvedena od teksturalnog staklenog vlakna, potpuno impregnirana teflonskom disperzijom i sa startnim (break-in) lubrikantom bez silikona.

### Osobine:

Zaptivna pletenica visoke gustine, gipka i fleksibilna, sa dobrom hemijskom otpornošću.

### Oblasti primene:

TEADIT 2026 se preporučuje za zaptivanje centrifugalnih i klipnih pumpi, ventila, mešača, agitatora itd., u naftnoj, prehrambenoj i hemijskoj industriji, šećeranama, postrojenjima za preradu vode, industriji celuloze i papira.

### Fluidi:

TEADIT 2026 se koristi za zaptivanje vode, pare, hemikalija, rastvarača, ulja, blažih kiselina i baza itd.



### Prednosti:

Tip 2026 je multi-funkcionalna zaptivna pletenica, koja može da se koristi u raznim aplikacijama unutar jednog postrojenja.

### Ne koristi se za:

Koncentrisane kiseline i baze, kiseonik.

Temperatura: - temp.: + temp.:  
(°C) 40 280

Pritisak: rotacioni: recipročni: statički:  
(bar) 15 20 150

pH: 3-12

Gustina:(g/cm<sup>3</sup>) 2

Brzina na vratilu:  
(m/s) 8

#### TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0  
A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20  
e-mail: mail@teadit-europe.com

#### TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911  
I-25030 Paratico Fax: +39 - 035 - 913060  
e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

