

Zaptivna pletenica tip 2048

prethodna oznaka 5003

Sastav materijala:

Zaptivač od kratkih aramidnih vlakana, grafitiziran i impregniran inertnim mazivom, dijagonalnog pletenja.

Osobine:

Veoma dugotrajna i izdržljiva pletenica, sa naknadnom grafitnom impregnacijom, kojom se poboljšava toplotna provodljivost u odnosu na konvencionalne aramidne zaptivače.

Oblasti primene:

Koristi se u statičkim i dinamičkim uslovima, kao što su klipne i centrifugalne pumpe, ventili, mikseri itd., u raznim industrijskim oblastima.

Fluidi:

Voda, kiseline i baze srednjeg intenziteta, razne hemikalije, slana i otpadna voda i slični abrazivni fluidi.



Prednosti:

Ekonomična multi-funkcionalna zaptivna pletenica.

Ne koristi se za:

Koncentrisane kiseline i baze, alkalne metale, kiseonik.

Temperatura: - temp.: + temp.:
(°C) 100 280

Pritisak: rotacioni: recipročni: statički:
(bar) 20 80 150

pH: 2-12

Gustina:(g/cm³) 1,2Brzina na vratilu:
(m/s) 20

TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0
A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20
e-mail: mail@teadit-europe.com

TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911
I-25030 Paratico Fax: +39 - 035 - 913060
e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

