

## Zaptivna pletenica tip 2077

### Sastav materijala:

Zaptivna pletenica TEADIT 2077 se proizvodi od PTFE vlakna sa inkorporisanim grafitom i lubrikovana je silikonskim uljem otpornim na visoke temperature.

### Osobine:

Odlična hemijska otpornost i nizak koeficijent trenja teflonskog vlakna, u kombinaciji sa dobrom toplotnom provodljivošću grafit, čine tip 2077 veoma upotrebljivim i korisnim zaptivačem.

### Oblasti primene:

Univerzalna zaptivna pletenica za pumpe, mikserne, agitatore, ventile itd. Idealna je za aplikacije gde se istovremeno javljaju visoke obimne brzine i visoke temperature.

### Fluidi:

Može se koristiti sa svim vrstama fluida i hemikalija, osim dole navedenih.



### Prednosti:

Zaptivna pletenica širokog spektra upotrebe sa odličnom hemijskom otpornošću. Zbog jedinstvenih karakteristika, preporučuje se upotreba ove pletenice na više aplikacija u okviru jednog postrojenja, čime se znatno smanjuje potreba za različitim tipovima zaptivača na lageru.

### Ne koristi se za:

Visoko oksidirajuće fluide kao što su oleum, carska vodica (aqua regia), isparljiva azotna kiselina, gasoviti fluorin, boje i lakovi, kiseonik.

Temperatura: - temp.: + temp.:  
(°C) 200 280

Pritisak: rotacioni: recipročni: statički:  
(bar) 20 80 150

pH: 0-14

Density:(g/cm<sup>3</sup>) 1,6

Brzina na vratilu:  
(m/s) 18

#### TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0  
A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20  
e-mail: mail@teadit-europe.com

#### TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911  
I-25030 Paratico Fax: +39 - 035 - 913060  
e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

