

Zaptivna pletenica tip 2422

Sastav materijala:

Dijagonalno ispletana zaptivna pletenica od prirodnog Ramie vlakna, gusto impregnirana PTFE komponentom i lubrifkovana inernim mazivom.

Osobine:

TEADIT 2422 odlikuje kombinacija odlične elastičnosti i fleksibilnosti sa niskim koeficijentom trenja. Posедуje FMPA atest za upotrebu sa prehrambenim proizvodima.

Oblasti primene:

Iako prvenstveno namenjena zaptivanju centrifugalnih i klipnih pumpi, primenu nalazi i kao zaptivač ventila. TEADIT 2422 se koristi u raznim industrijskim oblastima kao zaptivač za osetljive aplikacije i fluide koji ne smeju biti zaprljani. Industrija celuloze i papira, prehrambena industrija i brodogradnja su neke od tih oblasti. Pošto se Ramie vlakno ne raspada i ne rđa, tip 2422 je odlično rešenje za zaptivanje vratila na brodovima i čamcima.

Fluidi:

Hladna i topla voda, vodeni rastvori sa čvrstim česticama, šira, slana voda, celulozni fluidi, ulja, maziva itd.



Prednosti:

TEADIT 2422 je fleksibilna i elastična pletenica i jednostavno se ugrađuje. Izaziva neznatna oštećenja vratila (čaure). Pletenica TEADIT 2422 je odobrena od strane Nemačkog instituta FMPA za korišćenje sa prehrambenim proizvodima.

Ne koristi se za:

Kiseline i visoko koncentrisane baze, kiseonik.

Temperatura: - temp.: + temp.:
(°C) 130

Pritisak: rotacioni: recipročni: statički:
(bar) 20 20 30

pH: 5-11

Gustina:(g/cm³) 1,5

Brzina na vratilu:
(m/s) 10

TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0
A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20
e-mail: mail@teadit-europe.com

TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911
I-25030 Paratico Fax: +39 - 035 - 913060
e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

