

Zaptivna pletenica tip 2900

Sastav materijala:

TEADIT 2900 je proizvedena od Nylon 6 vlakna i impregnirana PTFE-disperzijom.

Osobine:

Veoma gipka pletenica, male specifične težine i sa dobrom toplotnom i hemijskom otpornošću.

Oblasti primene:

Za sporo obrtna vratila i statičke aplikacije u raznim industrijskim oblastima. Ovaj tip zaptivača je veoma popularan u industriji celuloze i papira, gde se koristi na centrifugama i sličnoj opremi.

Fluidi:

Koristi se u kontaktu sa slabim kiselinama i bazama, vodom, parom (do navedene temperaturne granice, za kratke periode do 115°C), slanu vodu, gasove, itd.



Prednosti:

Niska gustina rezultira u većoj metraži po kilogramu. Tip 2900 je mekana i savitljiva pletenica koja se veoma dobro prilagođava oštećenjima na zaptivnim površinama.

Ne koristi se za:

Koncentrisane kiseline i baze, kiseonik.

Temperatura: - temp.: + temp.:
(°C) 40 90

Pritisak: rotacioni: recipročni: statički:
(bar) 5 25

pH: 5 - 10

Gustina:(g/cm³) 1,1

Brzina na vratilu:
(m/s) 3

TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0
A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20
e-mail: mail@teaditeurope.com

TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911
I-25030 Paratico Fax: +39 - 035 - 913060
e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

